

## ABOUT US

Shanghai Wenyou Industry Co., Ltd. mainly engaged in the advanced materials of MV and HV insulation products for indoor and outdoor use, both suitable for APG and vacuum casting.

### Unique Core Competitiveness

- › Automatic production line with computer and robot.
- › Delivery within 7 working days.
- › High quality service with 0% complaint.
- › Yearly production capacity above 20K tons.

### High Quality Electrical Raw Materials

- Epoxy resin
- Hardener
- Release agent
- Color paste
- Silica powder
- Flexibilizer

## CONTACT US

上海稳优实业有限公司  
SHANGHAI WENYOU INDUSTRY CO.LTD

🏠 ADD: No.8 Lane 328,Minle Road,  
Fengxian District, Shanghai P.R.,  
China.

☎ TEL: +86(21) 57500369-841  
+86 18916511816

✉ EMAIL: info@sh-wysy.com

🌐 <https://sh-wysy.en.alibaba.com>



Whatsapp



上海稳优实业有限公司  
WENYOU SHANGHAI WENYOU INDUSTRY CO.LTD

至稳 / 至优 / 安全 / 专业 / 品牌  
*ALL FOR THE HIGH QUALITY*



WWW.WENYOU EPOXY.COM

THE BEST

WEN YOU

ELECTRICAL INSULATION MATERIALS

至稳 / 至优 / 安全 / 专业 / 品牌



## WENYOU EPOXY RESIN SYSTEMS SELECTION CHART

Applications	Product Designation	Manufacturing process	Mix ratio (Epoxy resin / Hardener / Filler)	Pot life	Indoor / Outdoor	DSC, Tg °C	Flammability	Crack resistance properties	Note
Current and Voltage transformers	8216X	Vacuum casting	100/100/300-350	70°C/75Min.	Indoor	60-80	/	8.3-8.7	Accelerator to be required.
	8216F	Vacuum casting	100/100/300-350	70°C/75Min.	Indoor	60-80	/	8.3-8.7	
	8217F	Vacuum casting	100/100/300-350	70°C/75Min.	Indoor	70-90	/	8.1-8.5	
	8228	Vacuum casting	100/100/0	70°C/75Min.	Indoor	100-120	/	8.6-9.0	Prefilled with filler
	9205	APG / Vacuum casting	100/100/300-450	35°C/7hrs. Or 70°C/75Min.	Indoor	65-115	/	7.0-8.8	Accelerator and flexibilizer to be required.
	9216F	APG	100/100/330-380	35°C/7hrs.	Indoor	60-80	/	8.3-8.7	
	9217F	APG	100/100/330-380	35°C/7hrs.	Indoor	70-90	/	8.1-8.5	
	9228	APG	100/100/0	35°C/7hrs.	Indoor	100-120	/	8.6-9.0	Prefilled with filler
	184	APG / Vacuum casting	100/80/300-450	7hrs. Or 70°C/75	Outdoor	65-105	/	7.0-8.8	Accelerator and flexibilizer to be required.
	8516	Vacuum casting	100/100/350-420	70°C/75Min.	Outdoor	60-80	/	8.6-9.0	
	9516	APG	100/100/350-450	35°C/7hrs.	Outdoor	60-80	/	8.6-9.0	
	9514	APG	100/100/350-450	35°C/7hrs.	Outdoor	70-90	/	8.3-8.7	
Dry type transformer	8276	APG	100/100/300-350	35°C/7hrs.	Indoor	70-90	6mm / V0	8.1-8.5	
	8276	Vacuum casting	100/100/300-350	70°C/75Min.	Indoor	70-90	6mm / V0	8.1-8.5	
Dry type transformer	8214	Vacuum casting	100/100/200-250	70°C/90Min.	Indoor	70-90	/	8.3-8.7	accelerator is required.
	8224	Vacuum casting	100/100/0	70°C/90Min.	Indoor	70-90	/	8.6-9.0	Prefilled with filler.
Bushings and Insulators	9287F	APG	100/100/350-450	35°C/7hrs.	Indoor	90-100	/	7.6-8.0	
	9219F	APG	100/100/350-400	35°C/7hrs.	Indoor	100-120	/	7.3-7.7	
	9215	APG	100/100/350-400	35°C/7hrs.	Indoor	110-125	/	7.0-7.4	
	9278	APG	100/100/300-350	35°C/7hrs.	Indoor	90-110	6mm / V0	7.8-8.2	
	9518	APG	100/100/350-450	35°C/7hrs.	Outdoor	90-110	/	7.8-8.2	
Embedded pole and solid insulation	9214	APG	100/100/350-400	35°C/7hrs.	Indoor	85-105	/	8.3-8.7	
	9218	APG	100/100/350-380	35°C/7hrs.	Indoor	95-115	/	8.1-8.5	
	9228	APG	100/100/0	35°C/7hrs.	Indoor	100-120	/	8.6-9.0	Prefilled with filler
	9514	APG	100/100/350-450	35°C/7hrs.	Outdoor	70-90	/	8.3-8.7	

## PRODUCT PACKAGE



### CERTIFICATE



### PROFESSIONAL PRODUCTION



**Export**

SHANGHAI WENYOU  
ELECTRICAL INSULATION MATERIALS